


Technical Data

September 24, 2024

Type	EC6 U0/ URS10			KURARAY TRADING CO.,LTD FUNCTIONAL MATERIALS DIVISION BELT PRODUCTS DEPT.		
Item		Unit	Contents		Remarks	
Specification	Composition		URS10 EC1 EC1 EC1 EC1 EC1 EC1		<Surface cover> Polyurethane 1.0mm <Core> Polyester woven fabrics 6ply	
	Total thickness		mm	6.4		
	Weight		Kg/m2	6.0		
Standard	Production range	Width	mm	2000		
		Length	m	100		
	Standard joint			Step skiving		
Performance	Tensile strength		N/mm	560	Head speed 30mm／min	
	The maximum elongation		%	40		
	Tension for 1% elongation		N/mm	22		
	Tension for 5% elongation		N/mm	92		
	Static frictional coefficient	Surface		0.45	HEIDON Tribogear μ S (Muse) TYPE : 94i	
		Back		0.21		
	Abrasion wear(Surface)		mg	5 ~ 15	Abrasion ring:H-22 Load 1kg 1000times	
	Minimum pulley Diameter		mm	150	Belt For Belt－Wrapper	
Continuous use temperature range		℃	-10 ~ 80			

* Numerical value and the contents in a list may be changed without a notice by quality improvement.